


Product overview

Plastic Modular Belt Series


Straight Running Belt Overview

<p>Pitch 8.00 mm (0.32 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>
<p>uni NTB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>2000 N/m (137 lbf/ft)</p>	<p>uni M-OWL Strength Index (POM)</p> <p>20000 40000 60000</p> <p>4500 N/m (309 lbf/ft)</p>	<p>uni M-QNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>19000 N/m (1302 lbf/ft)</p>	<p>uni M-SNB M3 Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15000 N/m (1028 lbf/ft)</p>
<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 19.1 mm (0.75 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>
<p>uni M-TTB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>22500 N/m (1541 lbf/ft)</p>	<p>uni Light Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (702 lbf/ft)</p>	<p>uni CNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15700 N/m (1076 lbf/ft)</p>	<p>uni JCB Y Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>
<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>
<p>uni LPB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>	<p>uni QNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>	<p>uni S-MPB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p>	<p>uni SNB M2 Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p>
<p>Pitch 27.9 mm (1.10 in)</p> <p>Running direction</p>	<p>Pitch 38.1 mm (1.50 in)</p> <p>Running direction</p>	<p>Pitch 38.1 mm (1.50 in)</p> <p>Running direction</p>	<p>Pitch 40.0 mm (1.57 in)</p> <p>Running direction</p>
<p>uni OWL Strength Index (POM)</p> <p>20000 40000 60000</p> <p>12000 N/m (822 lbf/ft)</p>	<p>uni Light EP Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (703 lbf/ft)</p>	<p>uni SSB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>36000 N/m (2467 lbf/ft)</p>	<p>uni ACB Strength Index (POM)</p> <p>20000 40000 60000 80000 100000</p> <p>90000 N/m (6169 lbf/ft)</p>



Straight Running Belt Overview




uni L-SNB
Strength Index (POM)




uni OPB
Strength Index (POM)





uni BLB
Strength Index (POM)



uni CPB
Strength Index (POM)





uni CSB
Strength Index (POM)




uni ECB
Strength Index (POM)




uni MPB
Strength Index (POM)




uni RTB M1
Strength Index (POM)



uni X-MPB
Strength Index (POM)




uni XLB
Strength Index (POM)





For further information,
please find the latest
version of our modular
datasheets at:
www.unichains.com



Side Flexing Belt Overview





uni Flex ASB
Strength Index (POM)




uni Flex OSB
Strength Index (POM)




uni Flex SNB
Strength Index (POM)




uni Flex ONE
Strength Index (POM)



uni Flex L-ASB
Strength Index (POM)



uni Flex L-OSB
Strength Index (POM)



Expert advice, quality solutions and local service for all your belting needs
www.ammeraalbeltech.com

Global Headquarters:
Ammeraal Beltech Holding B.V.
P.O. Box 38, 1700 AA Heerhugowaard
The Netherlands

T +31 72 575 1212
F +31 72 571 6455
info@ammeraalbeltech.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.